

## **You Bang Shou® YBS-BQH 72-102**

YBS-BQH 72-102 is a high-purity rolling bearing grease for long-term lubrication. It is low noise level rolling bearing grease. It has excellent performance characteristics thanks to a high-quality ester oil, a new polyurea thickener and special additives. It is special in that it combines high-temperature resistance and extreme purity.

### **Performance advantage**

- ◎- Cost savings due to long service life of grease at > 80°C.
- ◎- Smooth running, low noise.
- ◎- Wide service temperature range allows a variety of applications.
- ◎- Long bearing life due to excellent water resistance.

### **Typical data**

<b>Test items</b>	<b>You Bang Shou</b>	<b>Testing standards</b>
Chemical composition, thickener	polyurea	
Service temperature	-40 °C / -40 °F-180 °C / 356 °F	/
Colour	beige	/
Kinematic viscosity of the base oil, 100 °C	approx. 11 mm <sup>2</sup> /s	DIN 51562
Kinematic viscosity of the base oil, 40 °C	approx. 100 mm <sup>2</sup> /s	DIN 51562
Drop point, °C	250 °C	DIN ISO 2176
Density at 20 °C	0.99 g/cm <sup>3</sup>	/



**Dongguan Jialede Lubrication Materials Co.,Ltd**

**Shenzhen Jialede Chemical Technology Co.,Ltd**

Address: 302, Building 15, No. 142, Jinghai West Road, Chang'an  
Town, Dongguan City, Guangdong Province, China

Tel: 15767789227 Manager Zhu

18682086449 Huang Manager

---

## Application

YBS-BQH 72-102 is used for long-term or lifetime lubrication. Such applications include ball bearings in electric motors, fans, air conditioners, generators and belt tensioners in cars, power tool as well as household appliances and office equipment.

## Note

Remove as much contaminants and residue as possible before use, apply by rubbing, oil bath or spray. Do not mix with other oils.

The possibility of a change in colour is inherent in this product concept. It has, however, no influence on product performance.

## Packaging and storage

This product is available in 1kg tin cans, 0.5KG tin cans, 800g tubes, 10KG drums and 20KG drums. As well as personalised packaging according to customer requirements, OEM bespoke packaging.

\*Store in dry conditions, away from other flammable materials, heat sources and direct sunlight.